

Index for **"The Journeyman's Guide to Geometric Dimensioning and Tolerancing:
GD&T for the New Millennium"**

© Bryan R. Fischer - 2003-2007 - Advanced Dimensional Management Press

Additional tolerance (Bonus tolerance)	35-36, 124-126, 130-131, 134-135, 139-140, 143, 156, 158
defined	139-140
Ambiguity, Avoiding	1, 4, 137, 145, 215, 222
ASME Y14.5M-1994	
conventions	3
defaults	3, 15, 31-32, 34, 139, 174
definitions	29-31
fundamental rules	31-32
importance of	1
Basic Dimensions	6, 29, 37-39, 162-163, 164-173, 213-214, 227, 229-235
Boundary, inner	29
Boundary, outer	29
Chained Dimensions	37, 137
Circularity	5, 34, 85, 88-89
at a glance	88
Concentricity	5, 34, 85, 194, 196, 197
Converting +/- to positional tolerances	146-147
Coordinate systems	46, 49-50, 60-61, 68, 76-81, 159-163
Coplanarity - Controlling	63
Cylindricity	5, 34, 85, 90-91
at a glance	90
unit-basis	90
Datum Feature Simulators	29, 46-81, 148-154, 160, 210, 251
for Primary Datum Features	52-55, 72-74
Physical Datum Feature Simulators - Imperfect	52-55, 72
Precedence	51, 76-81, 148-154, 160
Simulated Datum and	72
Virtual Datum Feature Simulators - Perfect	29, 52-55
Datum Features	6, 8, 29, 34, 46-83, 120, 127, 132, 144, 148-154, 160, 174-179
Bounded	48, 64
Complex	48, 64, 65
Datum Feature Symbol	6, 7, 10, 62-64, 65, 257-259
Datum Features of Size	48, 51, 52-55, 62, 69-70, 73-75, 78-81, 82, 148-154, 204, 257-259
Datum Identifying Letter	48, 66
Definition	29, 46
Degrees of Freedom and	49, 52-55, 60-61, 68, 77, 79, 81
Functional	46
Labeling	62-64
Multiple Datum Features	63, 204
Partial	48
Planar	48, 51, 52, 62, 63, 72, 76-81
Precedence	9, 45, 51, 65, 68, 70, 76-81, 118, 120, 127, 132, 140, 148-154, 159-163, 198-199, 257-259
selection criteria	46, 48

Tolerancing (Qualifying)	52-55, 76, 78, 80, 82
Datum Reference Frames	9, 46-81, 86, 88, 90, 92, 120, 127, 132, 136, 194, 195, 198, 199, 213, 214
coordinate systems defined by	46, 49-50, 51, 60-61, 76-81, 160-163
Degrees of Freedom and	49, 52-55, 60-61, 68, 77, 79, 81
functional	46
Functional	46
in Composite Feature Control Frames	140-142, 217-218, 164-185, 229-235
Rules for	140
Precedence	9, 45, 51, 65, 68, 70, 76-81, 118, 120, 127, 132, 140, 148-154, 159-163, 198-199, 257-259
Datum Targets	29, 48, 65-67
Datum, Simulated	29, 46
Datums	8, 10, 29, 38-39, 40, 46-81, 120, 127, 132, 159-163, 257
Datum Feature Simulators and	46-47, 56-61, 72
Datum Features and	8-9, 46-48, 50-55, 56-81
Datum Reference Frames and	46-47, 51-55, 68, 76-81
Definition	29, 46
Feature Control Frames and	8-9, 140-141
Precedence	9, 45, 51, 65, 68, 70, 76-81, 118, 120, 127, 132, 140, 148-154, 159-163, 198-199, 257-259
Simulated	72
Degrees of Freedom	49-50, 52-55, 60-61, 68, 77, 79, 81, 141
Compared with 3-2-1	68
Dimension, Basic	29
Dimension, Reference	29
Dimensioning and tolerancing philosophy	1-4
avoiding ambiguity	1
functional dimensioning and tolerancing	4
Dimensioning Requirements	37-39, 65-66, 86, 88, 90, 92, 120, 127, 132, 136, 194, 195, 198, 199, 213, 214
Drawings	6
Envelope, Actual Mating	29-30, 40-45, 51, 73-74, 115-117, 118-119, 159-163
Related to a Datum Reference Frame	40-45, 51
Related to the Feature	40-45, 51
Feature Control Frames	3, 6-10, 33, 34, 86, 88, 90, 92, 120, 127, 132, 136, 140, 142, 164-173, 174-179, 188-189, 194, 195, 198, 199, 213, 214, 217, 257-259
BOUNDARY with	27, 118, 120, 127, 132, 136, 138
Compartments	8-10
Composite	10, 86, 92, 95, 136, 140-142, 164-185, 213, 214, 229-239
Linking Lower Segments of	174-179
Contents	3, 7-10
Datum Feature Symbol and	62-64
INDIVIDUALLY with	257-259
Modifiers in	8, 9, 33-34
Multiple Segments (more than two)	140
on the drawing	6
projected tolerance zones in	10
SEP REQTS with	175-176
SIM REQTS with	174-179

Single Segment	7-10, 86, 88, 90, 92, 95, 120, 127, 132, 136, 194, 195, 198, 199, 213, 214
Feature of Size	6, 8, 15-28, 30, 48, 51, 52-55, 62, 69-70, 73-75, 78-81, 82, 92, 94, 95, 97-108, 109, 118, 120, 127, 132, 137-142, 144, 148-154, 204, 257-259
as Datum Features of Size	48, 51, 52-55, 62, 69-70, 73-75, 78-81, 82, 148-154, 204, 257-259
Axes of	115-117
definition of	30
in Functional Gages	148-154
Material Condition Modifiers and	33, 35-36
positional tolerance and	136, 137-140
rule #1 and	15-28
Tolerance Zones for	109
Allowable Variation in	110-114
Virtual Condition of	97-108
Feature, Axis of	30
Feature, Center Plane of	30
Feature, Derived Median Line of	30
Feature, Derived Median Plane of	30
Features	1-2, 6, 15-28, 29, 46, 48, 51-55, 62-64
bounded	27-28, 33, 118, 120, 127, 132, 136, 137-138
definition of	30
Fixed fastener situation	187
formulas	187, 191-193
orientation tolerance and	188
positional tolerance and	187, 188
projected tolerance zone and	187
Fixtures	46, 148-154
Flatness	86-87
and composite feature control frames	86
at a glance	86
Floating fastener situation	186
formula	186
positional tolerance and	186
Form Tolerances	5, 34, 86-96
Circularity	88-89
At a glance	88
unit-basis	88
Cylindricity	90-91
At a glance	90
unit-basis	90
Flatness	86-87
and composite feature control frames	86
At a glance	86
Rule #1 and form control	15-24
Straightness	92-96
and composite feature control frames	92, 95
At a glance	92
derived median line and	94

in two directions	96
lines elements and	93
material condition modifiers and	92, 94
RFS vs. MMC	94
unit-basis	92, 95
view dependency and	96
Format, plus/minus tolerances	11
dimensional limits and	11-13
effect on manufacturing process	12
effect on target value	12
equal bilateral	11-12
leading zeroes	11
legal differences	12
limit dimensions	11-12
number of decimal places	11
SPC and	12
trailing zeroes	11
unequal bilateral	11-12
unilateral	11-12
Free-State and Restrained Parts	32, 247-256
Default condition per ASME Y14.5M-1994	32
Deformation Due to Assembly Forces	247-255
Distinction Between Rigid and Non-Rigid	247
Flexible Gasket Example	256
Free State Symbol	33-34, 248
Functional Dimensioning and Tolerancing and	247-255
Invoking Free State on a Non-Rigid Part Drawing	248
Non-Rigid Parts	32, 247-248
Adjustment Note for Non-Rigid Parts	256
Restraint Forces	247-248
Restraint Notes	248, 255
Rigid Parts	32, 247
Full Indicator Movement (FIM)	30, 200, 205
Functional dimensioning and tolerancing	4
Functional Gaging	46, 148-154
Fundamental Rules	31-32
GD&T, Comparison with +/-	137, 145-147
GD&T, definition of	1
Geometric Characteristic Symbols	5
Geometry, types of	2
Individual	257-259
Journeyman's Guide, intent	1
Justification for GD&T	i, 1, 35-36, 44, 109, 115, 137, 215
Material condition modifiers	30, 33, 35-36, 92, 94, 124-126, 130-131, 134-135, 136, 139-140, 143, 148-154, 155, 156-158,
Additional (bonus) tolerance and	35-36, 124-126, 130-131, 134-135, 139-140, 143, 156-158
choosing the correct modifier	35-36, 156-158
alignment	157
combination of factors	157

edge distance or wall thickness	156
fit or clearance	156
selection criteria	156-158
Default	36, 139
difference between the material condition modifiers	35-36
effect on tolerance zone	35-36
LMC	8, 15-27, 30, 33-36, 84, 86, 92, 100-102, 106-108, 120, 127, 132, 136, 138-140, 156-158, 196, 198, 199, 213, 214
and internal and external features	35-36, 97-108
definition of	35-36
MMC	8, 15-27, 30, 33-36, 51, 54-55, 84, 86, 92, 94, 97-99, 103-105, 120, 124-126, 127, 130-131, 132, 136, 138-142, 143, 148-154, 155, 156-158, 188, 196, 198, 199, 213, 214
and internal and external features	35-36, 97-108
definition of	35-36
RFS	9, 30, 33-36, 48, 51, 52-54, 73-74, 85, 86, 88, 90, 92, 94, 120, 123, 126, 127, 129, 132, 133, 136, 139, 156-158, 159-163, 188, 194-196, 198, 199, 213, 214
ANSI Y14.5M-1982	35
as a subset of MMC and LMC	36, 139
definition of	35-36
symbols for	33, 35
Orientation Tolerances	5, 34, 118-135
Angularity	
At a glance	132
By Element	118
Comparison of the Orientation Tolerances	118
Features of Size and	118, 120, 123-126, 127, 129-131, 132, 134-135
Parallelism	
At a glance	127
Perpendicularity	
At a glance	120
Planar Features and	120, 121-122, 127, 128, 132, 133
Related to more than one Datum	118, 120, 122, 127, 132
Plane, Tangent	30
Positional Tolerances	5, 34, 136-193
Additional (bonus) tolerance and	139-140, 143, 156
At a glance	136
BOUNDARY with	136, 137-138
Circumscribing a cylindrical positional tolerance zone about a square +/- tolerance zone	146-147
Compared to +/-	137, 145-147
Composite Position	136, 140-142, 164-185
Concentricity and	194
Converting +/- to Positional Tolerances	146-147
Datum Reference Frames and	136, 137-142, 148-154, 159-163, 164-185
Evaluating a Positional Tolerance Specification	159-163
Features of Size and	97-108, 109-114, 115-117
Functional Gaging and	148-154
History of	137
in Fixed- and Floating-Fastener Formulas	186-193

Material Condition Modifiers and	136, 139-140, 143, 148-154, 155, 156-158
Projected Tolerance Zones and	136, 187, 188-193
Separate Requirements and	175-176
Simultaneous Requirements and	174-179
Surface vs. Axis	139
Symmetry and	195
Tolerance Zone Geometry for Features of Size	109-114
Virtual Condition and Resultant Condition and	97-108
Zero Positional Tolerance	155
Profile Tolerances	5, 34, 213-246
All-Around	227
Avoiding Guesswork with	215
Avoiding Combining +/- and Profile	213-215
Basic Dimensions and	213-215
Benefits of	213-218, 219
Complex Surfaces and	213-218, 219, 229-235
Composite Profile	213-214, 217-218, 229-239
Unilateral Composite Profile	236-239
With Sim Reqts Specified	232-234
Without Sim Reqts Specified	229-231, 235
Coplanarity - Controlling	63
Datum Reference Frames and	213-214, 217,
Defining the Extents of Application	222
Direction of Tolerance	215
Equal Bilateral	215, 223
Limited Application	216-217, 228
Between Points	217, 228
Limited Area of Application	216
Limited Length of Application	216
Profile of a Line	5, 34, 215-218, 220, 221, 231, 240-246
ASME Y14.5M-1994 vs. ASME Y14.5.1M-1994 Interpretations	240
At a glance	213
Compared with Profile of a Surface	221
Composite Feature Control Frames and	213
What it Really Means	240-246
Profile of a Surface	5, 34, 214-218, 229-239
At a glance	214
Compared with Profile of a Line	221
Composite Feature Control Frames and	214, 229-239
Similarities to +/-	215
Simultaneous Requirements and	218, 232-234
Without Sim Reqts Specified	235
Tolerance Zones	215-216, 219-221, 223-228, 229-239
True Profile and the Profile Tolerance Zone	215
Types of Control	213-218
Unequal Bilateral	215, 224
Unilateral	215, 225-226
Unit Basis	218

Universal Applicability of	213-215
Projected tolerance zones	10, 33-34, 136, 187, 188-193
effect inside and outside the part	190
formulas to calculate equivalent tolerance when projected tolerance is not specified	191-193
in fixed fastener calculations	187
methods of specifying	188-189
reasons for	188-189
reluctance of companies to use	188
Symbol	10, 33-34
Threaded Holes and	187, 188-193
Radius Dimensions	14
Reference Dimensions	6
Repetitive Datum Reference Frames	257-259
Individual, Use of	257-259
Resultant Condition	30, 97-108
Rule #1	15-28, 84, 116
Violation of	15, 94, 95
Runout tolerances	5, 34, 198-212
Circular Runout	198, 200-202, 206-207, 209-212
And Inspection	200
Circular Runout vs. Total Runout	198, 199, 209
Form Error vs. Location Error	210-212
Full Indicator Movement (FIM)	30, 200, 205
Multiple Datum Feature and	204
Surfaces of Revolution and	203
Total Runout	
And Inspection	201-202
Separate requirements	174-176
Invoking	175-176
Simultaneous requirements	164, 169, 174-179, 180-185, 218, 229-235
Default condition per ASME Y14.5M-1994	174
Invoking	174-179, 180-185
Overriding	175-176
Size, Actual	30
Size, Actual Local	15-24, 31
Size, Actual Mating	15, 31, 35-36, 139-140, 156-157
Size, Limits of	11-13, 15-24, 31
Size, Nominal	31
Size, Resultant Condition	31
Size, Virtual Condition	31
Straightness	92-96
and composite feature control frames	92, 95
at a glance	92
derived median line and	94
in two directions	96
lines elements and	93
material condition modifiers and	92, 94
RFS vs. MMC	94

unit-basis	92, 95
view dependency and	96
Surfaces of Revolution	203
Symbology	3, 5-10, 62, 65-66
Symmetry	5, 34, 195, 196-197
Tolerance	31
Tolerance, Bilateral	31
Tolerance, Geometric	31
Tolerance, Unilateral	31
True Geometric Counterpart	31
True Position	31
Units	3
Virtual Condition	31, 94, 97-108